



Chelan County Fire Marshal's Office

Fire Protection Credits Form

Owner Name	Address or Parcel#	Points
Water Supply Credits		
<input type="checkbox"/> Approved Fire District Water Supply (property is within and served by a Fire District)		6
<input type="checkbox"/> Structures not in or served by a Fire District <u>without</u> an approved fire sprinkler system per NFPA 13, 13R or 13D as applicable, must provide a stored water supply based on NFPA 1142		6
<input type="checkbox"/> Structures not in or served by a Fire District <u>with</u> an approved fire sprinkler system per NFPA 13, 13R or 13D as applicable, must provide a stored water supply of 50% as based on NFPA 1142		6
Total Water Supply Credits (Minimum of 6 points required)		_____
Setback Credits		
<input type="checkbox"/> 30' Minimum setback all Property Lines		1.5
<input type="checkbox"/> 60' Minimum setback all Property Lines		2
<input type="checkbox"/> 100' Minimum setback all Property Lines		2.5
(Only one allowed)		
Total Setback Credits (Minimum of 1.5 points required, unless lot is too small then additional building credits will be required with approval by the Fire Marshal)		_____
Building Credits		
<input type="checkbox"/> Building < 2,000 sq. ft.		1
<input type="checkbox"/> Monitored fire alarm with smoke detectors (may be home fire/security)		.5
<input type="checkbox"/> ½" Gypsum board on all interior walls (create thermal barriers)		1
<input type="checkbox"/> Eaves and soffits protected on the exposed underside by 2" nominal lumber or approved non-combustible materials.		.5
<input type="checkbox"/> Gutter and downspouts – constructed of noncombustible material and an approved method to prevent the buildup of debris in the gutter		.5
<input type="checkbox"/> Exterior walls meeting one of the following: 1-Hr rated construction assembly. Approved non-combustible materials. Heavy timber or log wall construction. Fire retardant treated wood (labeled for exterior use)		1
<input type="checkbox"/> Under floor meeting one of the following: Enclosed to the ground with exterior walls. Limited enclosure where all exposed structural columns, beams and supporting walls are protected by 1-Hr fire resistive rated construction. Approved non-combustible materials Heavy timber or log construction. Fire retardant treated wood (labeled for exterior use)		1
<input type="checkbox"/> Exterior Doors and Windows: minimum 20-minute rating (not part of 1-Hr fire resistive rated construction exterior walls)		.5
<input type="checkbox"/> Vents: Attic ventilation openings, foundation or underfloor vents, or other ventilation openings in vertical exterior walls and vents through roofs shall not exceed 144 square inches each. Such vents shall be covered with noncombustible corrosion-resistant mesh with openings not to exceed 1/8 inch		1
Total Building Credits (Minimum of 2.5 points required)		_____
Total Fire Protection Credits (Minimum of 10 Required)		_____
Owner Signature:	Date:	_____